


# EC TYPE-EXAMINATION CERTIFICATE

according to Marine Equipment Directive (Module B)



NOTIFIED BODY 0809

This is to certify that the examined product with type designation

## OTEX ADHESION PRIMER

meets

the requirements imposed in IMO FTPC, Part 2, Part 5 and Annex 2 (IMO Resolution MSC.61(67) Annex 1 Part 2 and 5 and Annex 2) on **materials with low flame-spread characteristics and not producing excessive quantities of smoke and toxic products or not giving rise to toxic hazards at elevated temperatures and**

the provisions of Marine Equipment Directive (96/98/EC, amendments 98/85/EC, 2001/53/EC and 2002/75/EC) that apply to **surface materials with low flame-spread characteristics.**

Manufacturer of the product is


**Tikkurila Paints Oy.**

The Certificate is valid until 26 January 2009.



Matti Lanu  
Research Manager

Espoo 26 January 2004



Jarmo Ruohomäki  
Senior Research Scientist

Manufacturer	Tikkurila Paints Oy Kuninkaalantie 1 FIN-01301 Vantaa Finland
Product	Otex Adhesion Primer
Product description	Resin based Adhesion Primer for priming and undercoating new and previously painted surfaces.
Approved application	On non-combustible substrates with a density of $480 \text{ kg/m}^3$ or higher and a thickness of 12 mm or greater. Dry film thickness of the paint max. 50 $\mu\text{m}$ and quantity of dry paint max. $120 \text{ g/m}^2$ .
Technical document	Otex Adhesion Primer product specification of Tikkurila Paints Oy 10 December 1997.
Test report	Test Report RTE1351/02, 22 April 2002, VTT Finland. Inspection Report RTE1355/02 22 April 2002, VTT Finland.
Test method	IMO FTPC Part 5 (IMO Resolution MSC.61(67) Annex 1 Part 5) - Test for surface flammability (test procedure IMO Resolution A.653(16)).

END OF CERTIFICATE

