


EC TYPE-EXAMINATION CERTIFICATE

according to Marine Equipment Directive (Module B)



NOTIFIED BODY 0809

This is to certify that the examined product with type designation

JALO MAT LACQUER

meets

the requirements imposed in IMO FTPC, Part 2, Part 5 and Annex 2 (IMO Resolution MSC.61(67) Annex 1 Part 2 and 5 and Annex 2) on **materials with low flame-spread characteristics and not producing excessive quantities of smoke and toxic products or not giving rise to toxic hazards at elevated temperatures** and

the provisions of Marine Equipment Directive (96/98/EC, amendments 98/85/EC, 2001/53/EC and 2002/75/EC) that apply to **surface materials with low flame-spread characteristics.**

Manufacturer of the product is

Tikkurila Paints Oy.

The Certificate is valid until 26 January 2009.

Espoo 26 January 2004



Matti Lanu
Research Manager



Jarmo Ruohomäki
Senior Research Scientist

| | |
|----------------------|---|
| Manufacturer | Tikkurila Paints Oy Kuninkaalantie 1 FIN-01301 Vantaa Finland |
| Product | Jalo mat lacquer |
| Product description | Alkyd lacquer for walls, ceilings and doors. |
| Approved application | On non-combustible substrates with a density of 2020 kg/m ³ or higher and a thickness of 3 mm or greater, and on any metallic substrate with a thickness of 2,25 mm or higher. Dry film thickness of the paint max. 20 µm. |
| Technical document | Jalo mat lacquer product specification of Tikkurila Paints Oy 27 October 2003. |
| Test report | Test Report RTE187/00, 31 January 2000, VTT Finland. Inspection Report RTE400/00 31 January 2000, VTT Finland. |
| Test method | IMO FTPC Part 5 (IMO Resolution MSC.61(67) Annex 1 Part 5) - Test for surface flammability (test procedure IMO Resolution A.653(16)). |

END OF CERTIFICATE

